

Gas Leak Detector

LD239



Gas leaks can cause detector noise and baseline instability, shorten column life and waste expensive carrier gas. GL Sciences' LD239 leak detector is an easy way to quickly identify leaks in your system.

LD239 provides the most sensitive He leak detection available in an inexpensive, compact, easily charged (via USB), and easy to use configuration.

Specifications

Detection Method	: Thermal conductivity
Target Gases	: Helium, CO ₂ , Ar, Ne etc (gases that are largely different from referential gas) ※Not for flammable and corrosive gases
Sensitivity (He)	: [Standard range] 0.005mL/min at minimum [High range] 0.0005mL/min at minimum
Display	: LCD
Temperature Range	: 10 - 40 °C
Battery	: Lithium ion battery installed, rechargeable through a USB port, 2.5 hours for a full recharge. 5 hour battery life with continuous use
Dimension	: 50 (W) x 20 (D) x 111 (H) mm
Weights	: 95g
Accessories	: USB cable (1M), Sample gas filter (probe built-in), referential gas filter (built-in), instruction manual, warranty certificate

Description	Cat.No.
Gas Leak Detector LD239	2702-19340
Battery for LD239	2702-19341
USB cable	2702-19331
Sample Filter	2702-19333
Reference Filter	2702-19334

Worldwide Ordering Information

GL Sciences, Inc. USA
4733 Torrance Blvd. Suite 255
Torrance, CA 90503
Phone: 310-265-4424
Fax: 310-265-4425
Email: info@glsciencesinc.com
Web: www.glsciencesinc.com

GL Sciences B.V.
De Sleutel 9
5652 AS Eindhoven
The Netherlands
Phone: +31 (0)40 254 95 31
Fax: +31 (0)40 254 97 79
Email: info@glsciences.eu
Web: www.glsciences.eu

GL Sciences, Inc. Japan
22-1 Nishishinjuku 6-Chome
Shinjuku-ku, Tokyo,
163-1130, Japan
Phone: +81-3-5323-6620
Fax: +81-3-5323-6621
Email: world@glsciences.com
Web: www.glsciences.com



International Distributors
Visit our Website at
www.glsciences.com/distributors